

4&8^{FT} LED Strip Fixture

Engineered for high efficiency and versatility, this LED Linear Strip Fixture is ideal for new construction or fluorescent strip replacements. Designed for surface-mounted or suspended installations, it delivers reliable low-constant current driver for safety, energy savings, and longevity. Featuring 0-10V dimming, selectable wattage and CCT, and optional motion sensor, this fixture adapts to various applications, including hospitals, schools, and retail spaces.

KEY FEATURES:


- **Power Adj. 4^{FT} 46W / 8^{FT} 90W and CCT (3500K/4000K/5000K)**
- **High Lumen Efficacy 130lm/w**
- **Milky frosted lens (acrylic PMMA) with durable 0.6mm white cold-rolled steel housing**
- Internal color selector switch
- Slim end cap enables seamless 8ft row mounting with connector kit for continuous installation
- Integrated LED gear tray and lens for quick installation
- No flicker, mercury free, instant on

APPLICATION

- Hallways
- Storage areas
- Common areas
- Walkways
- Utility rooms
- Stairwells



DIMENSION



SPECIFICATIONS

Luminous Efficacy	130lm/W
CCT	3500K/4000K/5000K (Selectable)
CRI	>Ra80
Beam Angle	110°
Input Voltage	120-347V
Auxiliary Output	12V
IP Rating	IP20
L70 Lifespan	50,000 Hours
Chipset	SMD2835
Dimmable	0-10V Dimmable
Operating Temp.	-20°C ~+45°C
Warranty	5 Year Warranty
Certifications	DLC Premium, ETL

MODEL NO.	DLC ID	WATTS	LUMENS	CCT(K)	PF	MOL	CASE QTY.
LIA-SF4-46W-3CCT-HV	S-L4VZX1	46/38/30	5980/4940/3900	3500/4000/5000 (K)	0.9	44.53x2.62x2.69	1 pc/box
LIA-SF8-90W-3CCT-HV	S-KW9886	90/75/65/55	12600/10500/9100/7700	3500/4000/5000 (K)	0.9	88.98x2.62x2.69	6 pcs/ctn (4ft) 2 pcs/ctn (8ft)
Optional Accessories		Additional Info:		DLC ID 4 ^{FT} : S-L4VZX1 Premium: Stairwell and Passageway Luminaires S-Q790HY Standard: Direct Linear Ambient Luminaires S-NPDKNW Standard: Low-Bay Luminaires for Comm. and Ind. Buildings DLC ID 8 ^{FT} : S-KW9886 Premium: Stairwell and Passageway Luminaires S-L57B85 Standard: Direct Linear Ambient Luminaires S-2CLJY Standard: High-Bay Luminaires for Comm. and Ind. Buildings			
LIA-SF4-MWS		Microwave Motion Sensor		Surface Mount & Suspended.			
LIA-SF4/VT4-MWS-RC		Wireless Remote Control		Optional: Emergency battery backup, Wire			
LIA-SF4-8FT-CK		4ft to 8ft for Row Mounting Connector Plate		Guard, Suspension Cable, Suspension Chain.			