

4FT LED Vapour Tight

Built for efficiency and durability, this fixture delivers 140lm/W with power and color selectable options. Designed for tough environments, it features NSF and NEMA 4X certifications, an IP66 waterproof rating, and IK10 impact resistance. Its 5VA flame-resistant housing ensures safety, making it ideal for industrial, commercial, and food processing applications.

KEY FEATURES:

- **Power (46/38/30W) and CCT (3500K/4000K/5000K) Adjustable**
- **High Lumen Efficacy 130lm/w**
- **NSF/ANSI, NEMA 4X Certified**
- IK10 Vandal-proof housing for harsh environments
- IP66 Water resistant, dust-tight
- Internal color selector switch
- PC Housing and lens with stainless steel latches
- 5VA flaming resistant housing
- No flicker, mercury free, instant on

APPLICATION

- Parking Garages • Outdoor Canopies • Tunnels walkways
- Warehouse/Ind. • Food proc. plants • Stairwells



DIMENSION



46.65x4.17x3.35 IN

SPECIFICATIONS

Luminous Efficacy	130lm/W
CCT	3500K/4000K/5000K (Selectable)
CRI	>Ra80
Beam Angle	110°
Input Voltage	120-347V
IP Rating	IP66
Impact Resistance	IK10
L70 Lifespan	50,000 Hours
Chipset	SMD2835
Dimmable	0-10V Dimmable
Operating Temp.	-40°C ~+40°C
Warranty	5 Year Warranty
Certifications	DLC Premium, ETL, NSF/ANSI 2

MODEL NO.	DLC ID	WATTS	LUMENS	CCT(K)	PF	MOL	CASE QTY.
LIA-VT4-46W-3CCT-HV	S-8VRF3C	46 38 30	5980 4940 3900	3500K/4000K/5000K	0.9	46.65x4.17x3.35	1 pc/box 4 pcs/ctn
Optional Accessories LIA-VT4-MWS Motion Sensor LIA-SF4/VT4-MWS-RC Remote		Additional Info: Surface Mount & Suspended. Emergency battery backup kit (optional)		DLC ID: S-8VRF3C Premium: Low-Bay Luminaires for Commercial and Industrial Buildings S-35DGGQ0 Premium: Stairwell and Passageway Luminaires S-Y9HNW8 Standard: Direct Linear Ambient Luminaires			